

# Cheek Riser/Rest Install Instructions

1. Support your rifle so the stock is not on an angle and clean the mounting area of your stock to remove any grease and dirt.
2. Install the bolt in to your breach and ensure you have no ammunition in your rifle.
3. Place the cheek riser on the area of your stock you would like to secure it too.
4. Check your shooting position to ensure that it is in the correct place.
5. Check that your bolt can be removed comfortably in the position you have put the cheek riser
6. **Short term install:** Peel back the yellow tape cover and mount in place.
7. **Long term install:** We have supplied two different sized self tapping screws (16mm & 25mm). Use the screw most suited for your stock. If you are worried about your stock splitting, then you should drill a pilot hole first. Then peel back the yellow tape cover and mount in place. Screw the cheek riser down using the most suitable screw. Use enough force to secure it firmly. But do not over tighten, as you may crack your stock or the riser.
8. **When removing the front section,** you will need to hold the cheek riser as shown(8a & b) and pull the front section out. You will need to wiggle it left and right and then slide it away.

#### Package includes:

- Cheek Riser base section (with tape installed)
- Cheek Riser upper front section
- 1 x 8g 16mm self tapping screw
- 1 x 8g 25mm self tapping screw



# Some of our other products

Visit: <https://acculongrange.com>




**Sling Stud Picatinny rail adapter for rifle:**  
 Great for Atlas style QD Bipods.



**Swivel Stud Picatinny rail adapter for rifle & QR Harris style bipod adapter kit.**



**Atlas Style QD Bipods:**  
 As a kit with our Sling Stud Picatinny rail adapter or sold separately.



**Ruger 10/22 Barrel Bore guide: built in muzzle guard - clean your barrel safely.**

Protect the muzzle area and crown of your 17-22LR rifle. (rifle and cleaning rod not included)



Front removes to help you remove your bolt

**13,16,18mm Rifle Cheek Rest/Riser** with easy rifle bolt removal feature: 3D Printed: fits Tikka T3 and many more. Less than 45 grams!!!



**QD Bipod Sling & Harris Bipod Adapter for Picatinny Weaver Rails.**



**Flip open Flexi Scope Cover - 30mm-58mm**  
**\*\*You Choose Size\*\***

Made from the latest TPU-E flexible composite to protect your scope from bumps and dirt. They are also shower proof and stealthy when opened.